

ADDITIVE SELECTION CHART

AUTOMOTIVE COATINGS

DEFOAMING

PIGMENT STABILIZING

LEVELING



Automotive OEM coatings (1/4)

Electrodeposition coatings

Application	Pigment stabilization, gloss, anti-flood, anti-float	Leveling	Anti-cratering, oil robustness	Substrate wetting	Defoaming	Increase of surface energy	Adhesion
Aqueous	BYK-DYNWET 800 DISPERBYK-109 DISPERBYK-111 DISPERBYK-192 DISPERBYK-2117	BYK-DYNWET 800 ●	BYK-326 ● BYK-327 ● BYK-3540 ●	BYK-347 ● BYK-349 ● BYK-3455 ●	BYK-011	Silicone-free: BYK-3560 Silicone: BYK-3565 BYK-3566	BYK-3560 ● BYK-4513*¹ ●

[•] First recommendation • Second recommendation * Please pre-neutralize before use.

For more products for electrodeposition coatings, please contact ecoat.byk@altana.com

Primer surfacers

Application	Pigment stabilization anti-flood, anti-float		Anti-settling Anti-sagging L	Leveling	Anti-cratering	Substrate wetting	Defoaming	Boiling marks, pinholes	Increase of electrical	Increase of surface energy	
	Colored and dark primer surfacers	Light and white primer surfacers								conductivity	
Solvent-borne	DISPERBYK-2055 DISPERBYK-2155 With high levels of BaSO ₄ : DISPERBYK-180	DISPERBYK-111 ODISPERBYK-180 O	RHEOBYK-7410 ET RHEOBYK-D 410	RHEOBYK-415 RHEOBYK-430 RHEOBYK-405	BYK-355 • BYK-358 N • BYK-399 •	BYK-322 • BYK-3550 •	BYK-3550 •	BYK-054 •	BYK-392 ● BYKETOL-OK ●	BYK-ES 80 (effective in the liquid coating)	BYK-3560 • BYK-3565 • BYK-3566 •
Aqueous	Grind with resin: DISPERBYK-180 DISPERBYK-2012 Resin-free grind: DISPERBYK-2010 DISPERBYK-2014	Grind with resin: DISPERBYK-180 DISPERBYK-2012 Resin-free grind: DISPERBYK-199 DISPERBYK-2010 DISPERBYK-2019	RHEOBYK-7420 ES RHEOBYK-7420 ET	RHEOBYK-440 ● RHEOBYK-H 7625 VF ●	BYK-381 • BYK-3560 • BYK-3565 •	BYK-349	BYK-346 BYK-347 BYK-349	BYK-011 BYK-015 BYK-024	BYKETOL-AQ BYKETOL-WA BYKETOL-WB BYK-015		BYK-3560 • BYK-3565 • BYK-3566 •

[●] First recommendation ○ Second recommendation

Automotive OEM coatings (2/4)

One-coat topcoats (solid colors)

Application	Pigment stabilization anti-flood, anti-float	, gloss,	Anti-settling A	Anti-sagging	Leveling	Anti-cratering	Substrate wetting	Surface slip	Defoaming	Boiling marks, pinholes	electrical
	Titanium dioxide, inorganic pigments	Organic pigments, carbon black									conductivity
Solvent-borne	Acidic surface: DISPERBYK-161*2 Acidic/basic surface: DISPERBYK-180 Basic surface: DISPERBYK-110 DISPERBYK-111 DISPERBYK-180	DISPERBYK-161*2 DISPERBYK-2013 DISPERBYK-2014 DISPERBYK-2200*2 DPP pigments: DISPERBYK-166 Combination with synergists: BYK-SYNERGIST 2100	RHEOBYK-7410 ET RHEOBYK-D 410	RHEOBYK-415 ● RHEOBYK-430 ● RHEOBYK-405 ○	Silicone-free: BYK-355 BYK-358 N BYK-399 Silicone: BYK-315 N BYK-320 BYK-331	BYK-306	BYK-306	BYK-306 ● BYK-378 ● BYK-3568 ● BYK-3760 ○	BYK-141 ●	BYK-352 • BYK-392 • BYKETOL-OK •	BYK-ES 80 (effective in the liquid coating)
Aqueous	Grind with resin: DISPERBYK-180 DISPERBYK-2012 Resin-free grind: DISPERBYK-190 DISPERBYK-2012 DISPERBYK-2018 DISPERBYK-2019	Grind with resin: DISPERBYK-184 DISPERBYK-2012 DISPERBYK-2014 Resin-free grind: DISPERBYK-190 DISPERBYK-2012 DISPERBYK-2014	RHEOBYK-7420 ES RHEOBYK-7420 ET	RHEOBYK-440 RHEOBYK-H 7625 VF	BYK-381 • BYK-3565 •	BYK-326	BYK-347 • BYK-349 • BYK-3451 • BYK-3455 •	BYK-331	BYK-011 • BYK-015 • BYK-1710 ○	BYKETOL-AQ BYKETOL-WA BYKETOL-WB BYK-015	

[●] First recommendation ○ Second recommendation

^{*2} In cases where the cationic groups of these additives interact with acidic components of the formulation (such as catalysts) DISPERBYK-170 is recommended instead.

Automotive OEM coatings (3/4)

Basecoats

Application	Pigment stabilization	n, gloss, anti-flood, anti-	float	Anti-settling	Leveling	Anti-cratering		Defoaming	Boiling marks,	Orientation of	Increase of
	Titanium dioxide, inorganic pigments	Organic pigments, carbon black	Effect pigments				wetting		pinholes	effect pigments	surface energ
Solvent-borne	DISPERBYK-110 DISPERBYK-180 DISPERBYK-2026	With CAB: DISPERBYK-2000 DISPERBYK-2001 Without CAB: DISPERBYK-161 DISPERBYK-2200 DISPERBYK-2200 Combination with synergists: BYK-SYNERGIST 2100	DISPERBYK-110 DISPERBYK-162	RHEOBYK-7410 ET RHEOBYK-D 410 Wax: CERATIX 8561 CERATIX 8563 CERATIX 8566	BYK-315 N ● BYK-320 ●	BYK-3550 ●	BYK-320	BYK-392 •	BYKETOL-OK ●	CERAFAK 103 CERAFAK 106 CERAFAK 110 CERATIX 8561 CERATIX 8563 CERATIX 8566	BYK-3565 • BYK-3566 •
Aqueous	Grind with resin: DISPERBYK-180 DISPERBYK-2012 Resin-free grind: DISPERBYK-190 DISPERBYK-2012 DISPERBYK-2019	Grind with resin: DISPERBYK-184 DISPERBYK-2012 DISPERBYK-2014 Resin-free grind: DISPERBYK-190 DISPERBYK-2012 DISPERBYK-2014 DISPERBYK-2014	DISPERBYK-180 DISPERBYK-192 DISPERBYK-2060	RHEOBYK-7420 ES RHEOBYK-7420 ET	BYK-381 • BYK-3560 •	BYK-326	BYK-347 • BYK-349 •	BYK-011	BYK-015 BYKETOL-AQ BYKETOL-WA BYKETOL-WB	AQUATIX 8421 • LAPONITE-RD • RHEOBYK-440 •	BYK-3565 • BYK-3566 •

[●] First recommendation ○ Second recommendation

Automotive OEM coatings (4/4)

Clearcoats

Application	Anti-sagging	Leveling	Anti-cratering	Substrate wetting	Scratch resistance (dry)	Surface slip	Defoaming	Boiling marks, pinholes	Increase of electrical conductivity	Increase of surface energy
Solvent-borne	RHEOBYK-415 ● RHEOBYK-430 ● RHEOBYK-405 ○	BYK-315 N • BYK-326 • BYK-358 N • BYK-399 • BYK-3550 •	BYK-306	BYK-306	NANOBYK-3650 NANOBYK-3652	BYK-306	BYK-141 ●	1-pack systems: BYK-390 • 2-pack systems: BYKETOL-OK •	BYK-ES 80 (effective in the liquid coating)	BYK-3568 ● BYK-3566 ○
Aqueous	RHEOBYK-H 7625 VF ●	BYK-381 • BYK-3565 •	BYK-326 • BYK-331 • BYK-333 • BYK-349 •	BYK-347 ● BYK-349 ●		BYK-331 • BYK-333 • BYK-378 •	BYK-011 • BYK-015 • BYK-1710 ○	BYKETOL-AQ BYKETOL-WA BYKETOL-WB BYK-015		BYK-3565 ● BYK-3566 ●

[●] First recommendation ○ Second recommendation

● First recommendation ○ Second recommendation

Automotive refinish coatings (1/4)

Putty

Viscosity reduction/increase of filler content	Air release	Rheology
BYK-W 969 Cobalt-accelerated systems: BYK-W 966 BYK-W 980 SYK-W 98	BYK-A 555 ●	CLAYTONE-VZ RHEOBYK-100 RHEOBYK-7503 RHEOBYK-7590 RHEOBYK-R 605 CLAYTONE-MPZ

Primer Surfacers

Application	Pigment stabilization, gl	oss, anti-flood, anti-float	Anti-settling	Anti-sagging	Leveling	Anti-cratering	Substrate wetting	Defoaming	Increase of
	Colored and dark primer surfacers	Light and white primer surfacers							surface energy
Solvent-borne	DISPERBYK-163 DISPERBYK-2055 DISPERBYK-2155	DISPERBYK-111 DISPERBYK-180	RHEOBYK-7410 ET RHEOBYK-D 410 ■	RHEOBYK-405 • RHEOBYK-415 • RHEOBYK-430 •	BYK-320 • BYK-355 • BYK-358 N • BYK-399 •	BYK-322 ● BYK-3550 ●	BYK-322 ● BYK-3550 ●	BYK-320 • BYK-392 •	BYK-3565 • BYK-3566 •
Aqueous	Grind with resin: DISPERBYK-180 DISPERBYK-2012 Resin-free grind: DISPERBYK-190 DISPERBYK-2010 DISPERBYK-2010 DISPERBYK-2012 DISPERBYK-2014	Grind with resin: DISPERBYK-180 DISPERBYK-199 Resin-free grind: DISPERBYK-190 DISPERBYK-2010 DISPERBYK-2012	RHEOBYK-7420 ES RHEOBYK-7420 ET RHEOBYK-H 7625 VF	AQUATIX 8421 • RHEOBYK-440 • RHEOBYK-H 7625 VF •	BYK-381 • BYK-3560 • BYK-3565 •	BYK-349	BYK-347 ● BYK-349 ●	BYK-011	BYK-3565 • BYK-3566 •

● First recommendation ○ Second recommendation

Automotive refinish coatings (2/4)

One-coat topcoats (solid colors)

Application	Pigment stabilization anti-flood, anti-float	, gloss,	Anti-settling	Anti-sagging	Leveling	Anti-cratering	Substrate wetting	Scratch resistance (dry)	Surface slip	Defoaming	Boiling marks, pinholes
	Titanium dioxide, inorganic pigments	Organic pigments, carbon black									
Solvent-borne	2-pack polyurethanes: DISPERBYK-110 DISPERBYK-180	2-pack polyurethanes: DISPERBYK-161 • DISPERBYK-2013 • DISPERBYK-2014 • DISPERBYK-2200 •	RHEOBYK-7410 ET RHEOBYK-D 410	RHEOBYK-415 RHEOBYK-430	BYK-320 • BYK-352 • BYK-358 N • BYK-399 •	BYK-306 • BYK-310 • BYK-378 •	BYK-306 • BYK-310 • BYK-378 •	NANOBYK-3650 NANOBYK-3652	BYK-306 • BYK-310 • BYK-378 • BYK-3760 •	BYK-141	BYK-392 BYKETOL-OK
	Thermoplastic acrylics: DISPERBYK-145 DISPERBYK-2001 DISPERBYK-2155	Thermoplastic acrylics: DISPERBYK-145 DISPERBYK-2001 DISPERBYK-2155								B1K-1000	
Aqueous	Grind with resin: DISPERBYK-180 DISPERBYK-2012	Grind with resin: DISPERBYK-184 DISPERBYK-2012 DISPERBYK-2014	RHEOBYK-7420 ES RHEOBYK-7420 ET	RHEOBYK-440 RHEOBYK-H 7625 VF	BYK-381 • BYK-3560 • BYK-3565 •	BYK-326 • BYK-331 • BYK-333 • BYK-3565 • BYK-3566 •	BYK-347 • BYK-349 • BYK-3451 • BYK-3455 •		BYK-331 • BYK-333 • BYK-378 •	BYK-011	BYKETOL-AQ BYKETOL-WA BYK-015
	Resin-free grind: DISPERBYK-190 DISPERBYK-2012 DISPERBYK-2018 DISPERBYK-2019	Resin-free grind: DISPERBYK-190 DISPERBYK-2010 DISPERBYK-2012 DISPERBYK-2014									

[●] First recommendation ○ Second recommendation

Automotive refinish coatings (3/4)

Basecoats

Application	Pigment stabilization	n, gloss, anti-flood,	anti-float	Anti-settling	Anti-sagging	Leveling	Anti-	Substrate	Defoaming	Boiling marks,	Effect pigment	Increase of
	Titanium dioxide, inorganic pigments	Organic pigments, carbon black	Effect pigments				cratering	wetting		pinholes	orientation	surface energy
Solvent-borne	DISPERBYK-110 DISPERBYK-180 DISPERBYK-2026	With CAB: DISPERBYK-2000 DISPERBYK-2001 Without CAB: DISPERBYK-161 DISPERBYK-2000 DISPERBYK-2013 DISPERBYK-2000	DISPERBYK-110 DISPERBYK-162	RHEOBYK-7410 ET RHEOBYK-D 410 Wax: CERATIX 8561 CERATIX 8563 CERATIX 8566	RHEOBYK-415 RHEOBYK-430	BYK-315 N ● BYK-320 ●	BYK-3550	BYK-320 • BYK-331 •	BYK-322 •	BYK-392 ●	CERAFAK 103 CERAFAK 106 CERAFAK 110 CERAFAK 110 CERATIX 8561 CERATIX 8563 CERATIX 8566	BYK-3566 • BYK-3568 •
Aqueous	Grind with resin: DISPERBYK-180 DISPERBYK-2012 Resin-free grind: DISPERBYK-190 DISPERBYK-2012 DISPERBYK-2018 DISPERBYK-2018 DISPERBYK-2019	Grind with resin: DISPERBYK-184 DISPERBYK-2012 Resin-free grind: DISPERBYK-190 DISPERBYK-2010 DISPERBYK-2012 DISPERBYK-2014	DISPERBYK-180 DISPERBYK-192 DISPERBYK-2060	RHEOBYK-7420 ES RHEOBYK-7420 ET	*	BYK-381 • BYK-3565 •	BYK-326	BYK-346 • BYK-347 • BYK-349 •	BYK-011	BYKETOL-AQ BYKETOL-WA BYK-015	AQUATIX 8421 • LAPONITE-RD • RHEOBYK-440 •	BYK-3565 • BYK-3566 •

• First recommendation • Second recommendation

Automotive refinish coatings (4/4)

Clearcoats

Application	Anti-sagging	Leveling	Anti-cratering	Substrate wetting	Scratch resistance (dry)	Surface slip	Defoaming	Boiling marks, pinholes	Increase of surface energy
Solvent-borne	RHEOBYK-415 ● RHEOBYK-430 ●	BYK-315 N • BYK-326 • BYK-355 • BYK-358 N • BYK-399 •	BYK-306	BYK-306	NANOBYK-3650 NANOBYK-3652	BYK-306	BYK-141 • BYK-392 • BYK-397 ○	BYK-352 ● BYKETOL-OK ●	BYK-3566 ● BYK-3568 ●
Aqueous	RHEOBYK-H 7625 VF	BYK-381 • BYK-3565 • BYK-326 ○	BYK-331	BYK-347 ● BYK-349 ●		BYK-331 • BYK-333 • BYK-378 ○	BYK-011	BYKETOL-AQ ● BYKETOL-WA ● BYK-015 ○	BYK-3565 • BYK-3566 •

[●] First recommendation ○ Second recommendation





BYK-Chemie GmbH Abelstraße 45 46483 Wesel Germany Tel +49 281 670-0 Fax +49 281 65735

info@byk.com www.byk.com ADD-MAX®, ADD-VANCE®, ANTI-TERRA®, AQUACER®, AQUAMAT®, AQUATIX®, BENTOLITE®, BYK®, BYK-AQUAGEL®, BYK®-DYNWET®, BYK-MAX®, BYK°-SILCLEAN®, BYKANOL®, BYKCARE®, BYKCTOL®, BYK)ET®, BYKO2BLOCK®, BYKONITE®, BYKOPLAST®, BYKUMEN®, CARBOBYK®, CERACOL®, CERAFAK®, CERAFLOUR®, CERAMAT®, CERATIX®, CLAYTONE®, CLOISITE®, DISPERBYK®, DISPERPLAST®, FULACOLOR®, FULCAT®, GARAMITE®, GELWHITE®, HORDAMER®, LACTIMON®, LAPONITE®, MINERPOL®, NANOBYK®, OPTIBENT®, OPTIFLO®, OPTIGEL®, POLYAD®, PRIEX®, PURABYK®, PURE THIX®, RECYCLOBLEND®, RECYCLOBYK®, RECYCLOSSORB®, RECYCLOSTAB®, RHEOBYK®, RHEOCIN®, RHEOTIX®, SCONA®, SILBYK®, TIXOGEL® and VISCOBYK® are registered trademarks of the BYK group.

The information herein is based on our present knowledge and experience. The information merely describes the properties of our products but no guarantee of properties in the legal sense shall be implied. We recommend testing our products as to their suitability for your envisaged purpose prior to use. No warranties of any kind, either express or implied, including warranties of merchantability or fitness for a particular purpose, are made regarding any products mentioned herein and data or information set forth, or that such products, data or information may be used without infringing intellectual property rights of third parties. We reserve the right to make any changes according to technological progress or further developments.

This issue replaces all previous versions.







